



GREENHUB 3



GREENHUB 3




KEY FEATURES



GreenHub 3 is designed for indoor and outdoor use to generate portable, off-grid electricity, producing only water and heat as byproducts.



It powers devices that use standard AC power (lamps, computers, tools, etc.).



Easy to use and featuring a small, compact design, the GreenHub 3 contains everything you need for a "full charge with complete autonomy."

TECHNICAL SPECIFICATIONS	500	1000	2000	3000	5000
Nominal AC Output Power	400 W	800 W	225 W	2400 W	4000 W (o fino a 4250 W)
Nominal DC Output Power	400 W	900 W	235 W	2700 W	4500 W
Max Power (5-second peak) AC	~500 W	1000 W	235 W	Da 2600 W a 3000 W	4500 W
Max Power (5-second peak) DC	~500 W	1000 W	245 W	Da 2600 W a 3000 W	4500 W
Main AC Outlet	220/230 V CA (50/60 Hz)	220/230 V CA (50/60 Hz)	Schuko AC outlet (110-230 V AC)	220/230 V CA (50/60 Hz)	220/230 V CA (50/60 Hz)
Main DC Output Jack	48 V CC	48 V CC	Connettore CC (12/24V CC)	48 V CC	48 V CC
AC auxiliary output	USB / 12V CC	USB / 12V CC	12/24 V CC	USB / 12V CC	USB / 12V CC
DC auxiliary output	USB / 12V CC	USB / 12V CC	12/24 v cc	USB / 12V CC	USB / 12V CC
AC Hydrogen Supply Pressure	6 - 25 bar	6 - 25 bar	6-25 bar (Ideal: 10.5 bar)	6 - 25 bar	6 - 25 bar
DC Hydrogen Supply Pressure	6 - 25 bar	6 - 25 bar	6-25 bar (Ideal: 10.5 bar)	6 - 25 bar	6 - 25 bar
Hydrogen Purity AC	99,995 % (min. 4.5)	99,995 % (min. 4.5)	99,995 % (min. 4.5)	99,995 % (min. 4.5)	99,995 % (min. 4.5)
DC Hydrogen Purity	99,995 % (min. 4.5)	99,995 % (min. 4.5)	99,995 % (min. 4.5)	99,995 % (min. 4.5)	99,995 % (min. 4.5)
AC System Interface	4.3-inch high-resolution LCD HMI display	4.3-inch high-resolution LCD HMI display	4.3-inch high-resolution LCD HMI display	4.3-inch high-resolution LCD HMI display	4.3-inch high-resolution LCD HMI display
DC System Interface	4.3-inch high-resolution LCD HMI display	4.3-inch high-resolution LCD HMI display	4.3-inch high-resolution LCD HMI display	4.3-inch high-resolution LCD HMI display	4.3-inch high-resolution LCD HMI display
Weight	23 Kgs	DC - 40 Kgs / AC - 43 Kgs	32 Kgs	AC - 79 Kgs / DC - 75 Kgs	AC - 94 Kgs / DC - 90 Kgs
Dimensions	400 x 600 x 250 mm	400 x 600 x 250 mm	600 x 400 x 250 mm	860 x 640 x 220 mm	1000 x 800 x 210 mm